HX Series

CHIP TYPE, 7000~10000 HOURS LONG LIFE ASSURANCE
貼片式，7000~10000 小時長壽命品



Long Life

- Wide temperature range -55~+105°C
  適用於-55~+105°C 的寬溫範圍
- Endurance 7000~10000 hours
  耐久性 7000~10000 小時
- RoHS & REACH compliant, Halogen-free
  符合 RoHS 與 REACH，無鹵

KL → Longer Life 長壽命化 → HX

□ SPECIFICATIONS 特性表

Items 項目	Characteristics 主要特性
Category Temperature Range 工作溫度範圍	-55 ~ +105°C
Voltage Range 額定工作電壓範圍	6.3 ~ 100V
Capacitance Range 靜電容量範圍	10 ~ 6800μF
Capacitance Tolerance 靜電容量允許偏差	±20% at 120Hz, 20°C
Leakage Current 漏電流	Leakage current ≤0.01CV or 3μA, whichever is greater (after 2 minutes application of rated voltage at 20°C) 漏電流 ≤0.01CV 或 3μA，取較大值（在 20°C 環境中施加額定工作電壓 2 分鐘後） C: Nominal capacitance (μF) 標稱靜電容量, V: Rated voltage (V) 額定電壓
Dissipation Factor (tan δ) 損耗角正切	Measurement frequency 測試頻率: 120Hz, Temperature 温度: 20°C

Rated Voltage (V) 額定工作電壓	6.3	10	16	25	35	50	63~100
tan δ (max.) 最大損耗角正切	0.32	0.30	0.26	0.18	0.16	0.14	0.12

Stability at Low Temperature 低溫特性

Measurement frequency 測試頻率: 120Hz

Rated Voltage (V) 額定工作電壓		6.3	10	16	25	35	50	63~100
Impedance Ratio 阻抗比 ZT/Z20 (max.)	Z(-25°C) / Z(+20°C)	3	3	2	2	2	2	2
	Z(-40°C) / Z(+20°C)	4	4	3	3	3	3	3
	Z(-55°C) / Z(+20°C)	8	8	6	5	4	3	4

Endurance 耐久性

When the capacitors are restored to 20°C after 10000 hours (7000 hours for ∅6.3×7.7 or ≥50V) application of the rated voltage at 105°C, they meet the characteristics listed below.
在 105°C 環境中施加額定工作電壓 10000 小時（∅6.3×7.7 或 ≥50V 為 7000 小時）後，待電容器恢復至 20°C 時進行測量，電容器的特性符合下表要求。

Capacitance Change 靜電容量變化率	Within ±30% of initial value 初始值的±30%以內
Dissipation Factor 損耗角正切	300% or less of initial specified value 不大於規範值的 300%
Leakage Current 漏電流	initial specified value or less 不大於規範值

Shelf Life 高溫貯存特性

When the capacitors are restored to 20°C after leaving under no load at 105°C for 1000 hours, they meet the specified value for endurance characteristics listed above.
在 105°C 環境中無負荷放置 1000 小時後，待電容器恢復至 20°C 時進行測量，電容器的特性符合耐久性特性中所列的規定值。

Resistance to Soldering Heat 耐焊接熱特性

(Please refer page 25 for soldering conditions)
(焊接條件請查閱第 25 頁)


After reflow soldering and restored at room temperature, they meet the characteristics listed below.
經過回流焊並冷卻至室溫後，電容器的特性符合下表要求。

Capacitance Change 靜電容量變化率	Within ±10% of initial value 初始值的±10%以內
Dissipation Factor 損耗角正切	initial specified value or less 不大於規範值
Leakage Current 漏電流	initial specified value or less 不大於規範值


Marking 標識 — Black print on the case top. 鋁殼頂部黑字印刷。

□ DRAWING 外形圖 (Unit: mm)

(∅6.3×7.7)



(∅8×10.5~∅16)



*1. Voltage mark for 6.3V is [6V] | 6.3V 的產品標識為 [6V]
*2. Applicable to ∅6.3×7.7 | 適用於∅6.3×7.7
*3. Applicable to ∅8×10.5~∅10 | 適用於∅8×10.5~∅10
*4. Applicable to ∅12.5~∅16 | 適用於∅12.5~∅16

Dimension table in next page.
尺寸表見下一頁。

Note: All design and specifications are for reference only and is subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.
注：以上所提供的設計及特性參數僅供參考，任何修改不作預先通知。如果在使用上有疑問，請在採購前與我們聯繫，以便提供技術上的協助。

HX Series

☐ DIMENSIONS (Unit: mm) 尺寸表

ØD x L	6.3 x 7.7	8 x 10.5	10 x 10.5/13.5	12.5 x 13.5/16	16 x 16.5	18 x 16.5/18.5/21.5
A	2.6	3.0	3.3	4.9	5.8	6.2
B	6.6	8.4	10.4	13.0	17.0	19.0
C	6.6	8.4	10.4	13.0	17.0	19.0
E ± 0.2	1.9	3.1	4.7	4.7	6.4	6.4
L	7.7	10.5	10.5/13.5	13.5/16.0	16.5	16.5/18.5/21.5
H	0.5~0.8	0.8~1.2	0.8~1.2	0.8~1.2	1.1~1.4	1.1~1.4

☐ DIMENSIONS & STANDARD RATINGS 規格尺寸及標準參數

WV / μF / Code 代碼		6.3		10		16		25	
		0J		1A		1C		1E	
33	330							6.3 × 7.7	300
47	470					6.3 × 7.7	300	6.3 × 7.7	300
100	101	6.3 × 7.7	300	6.3 × 7.7	300	6.3 × 7.7	300	6.3 × 7.7	300
220	221	6.3 × 7.7	300	8 × 10.5	600	8 × 10.5	600	8 × 10.5	600
330	331	8 × 10.5	600	8 × 10.5	600	8 × 10.5	600	10 × 13.5 (8 × 10.5)	600 (600)
470	471	8 × 10.5	600	8 × 10.5	600	10 × 10.5	850	12.5 × 13.5 (10 × 10.5)	950 (850)
680	681	10 × 10.5	850	10 × 10.5	850	10 × 10.5	850	12.5 × 13.5	950
1000	102	10 × 10.5	850	10 × 13.5	850	12.5 × 13.5 (10 × 13.5)	950 (850)	12.5 × 13.5	950
2200	222	12.5 × 13.5	950	12.5 × 16 (12.5 × 13.5)	1200 (950)	16 × 16.5	1450	18 × 16.5	1550
3300	332	12.5 × 13.5	950	16 × 16.5	1450	18 × 16.5	1550	18 × 21.5	2150
4700	472	16 × 16.5	1450	18 × 16.5	1550	18 × 18.5	2000		
6800	682	18 × 18.5	2000	18 × 21.5	2150			Case size 尺寸	Ripple current 紋波電流

WV / μF / Code 代碼		35		50		63		100	
		1V		1H		1J		2A	
10	100	6.3 × 7.7	300						
22	220	6.3 × 7.7	300	6.3 × 7.7	300			8 × 10.5	130
33	330	6.3 × 7.7	300	6.3 × 7.7	300	8 × 10.5	250	10 × 10.5	200
47	470	6.3 × 7.7	300	8× 10.5	350	8 × 10.5	250	12.5 × 13.5	850
100	101	8 × 10.5	600	10 × 10.5	670	10 × 10.5	400	12.5 × 16	950
220	221	10 × 10.5 (8 × 10.5)	850 (600)	12.5 × 13.5 (10 × 10.5)	850 (670)	12.5 × 13.5	850	18 × 16.5	1600
330	331	10 × 10.5	850	12.5 × 13.5	850	12.5 × 16	950	18 × 18.5	2000
470	471	12.5 × 13.5	950	16 × 16.5	1200	16 × 16.5	1450	18 × 21.5	2150
680	681	12.5 × 13.5	950	16 × 16.5	1450	18 × 16.5	1600		
1000	102	16 × 16.5 (12.5 × 16)	1450 (1200)	18 × 16.5 (16 × 16.5)	1600 (1450)				
2200	222	18 × 18.5	2000					Case size 尺寸	Ripple current 紋波電流

•Case size ∅D×L(mm), ripple current (mA rms) at 105°C, 100KHz •尺寸∅D×L(mm)，紋波電流(mA rms)於 105°C, 100KHz

☐ FREQUENCY COEFFICIENT OF ALLOWABLE RIPPLE CURRENT 紋波電流頻率補償系數

Frequency 頻率		50Hz	120Hz	300Hz	1KHz	10KHz~
Coefficient 系數	10 ~ 470μF	0.80	1.00	1.23	1.34	1.50
	680 ~ 6800μF	0.85	1.00	1.10	1.13	1.15

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5~10°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced. 鋁電解電容器在疊加紋波電流後會引起發熱，溫度每上升 5~10°C 壽命會減半。若要保持長壽命性能，請在使用過程中適當降低紋波電流。

- Taping specifications are given in page 19. 編帶標準請查閱第 19 頁。
- Soldering conditions and recommended land size are given in page 25. 焊接條件及推薦安裝尺寸請查閱第 25 頁。
- Please refer to page 20 for the minimum package quantity. 最小包裝數量請查閱第 20 頁。
- Please refer to page 18 for the Part Number System. 產品編碼規則請查閱第 18 頁。

Note: All design and specifications are for reference only and is subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.
注：以上所提供的設計及特性參數僅供參考，任何修改不作預先通知。如果在使用上有疑問，請在採購前與我們聯繫，以便提供技術上的協助。